






















# AMERICAN<sup>®</sup> PERFORMANCE SERIES

brand *Featuring Tapes You Can Rely On*

	FEATURE	MAX TEMP. FOR CLEAN REMOVAL	STRENGTH	CONFORMABILITY	MARKET
<b>PG21</b> <b>PREMIUM GRADE</b> 	Improved Temperature Range	 325°F	 Best		 
<b>OM</b> <b>PREMIUM GRADE</b> 	High Temperature Range & Smooth Backing	 250°F	 Better		
<b>AM</b> <b>MEDIUM GRADE</b> 	Improved Conformability	 225°F	 Better		
<b>GT</b> <b>INDUSTRIAL GRADE</b> 	Transparent & Clean One-Piece Removal	 225°F	 Better		



## PG21 HIGH TEMPERATURE

- Fine structured crepe backing sets the standard for sharp paint lines
- Resists paint-bleed through
- Specifically designed adhesive formula to ensure superior adhesion to a variety of surfaces
- High temperature resistances with 3-day UV properties



## GT TRANSPARENT, ONE-PIECE CLEAN REMOVAL

- Transparent backing to ensure all critical areas are protected
- Strong backing to ensure one-piece clean removal
- Specially formulated to provide a secure bond and to prevent lifting and overspray
- Easy and consistent unwinds to enhance the application process



## OM UV RESISTANT

- Exceptional conformability
- Excellent adhesion to backing to provide a secure bond and to prevent lifting and overspray
- Removes cleanly and provides a clean crisp paint line
- 3-day UV resistance



## AM HIGH CONFORMABILITY

- Excellent conformability to a variety of surfaces
- Enhanced vibrant aqua backing for high visibility of masked surfaces
- Resists paint flaking and wet sanding